

reset SG300-10



context

dit document beschrijft hoe Cisco SG300-10 switch reset naar fabrieksinstellingen

stappenplan

- verbind de switch met je laptop ahv [console](#)
- start de switch op
- druk met een paperclip de **reset**-knop ingedrukt

A screenshot of a PuTTY terminal window titled "COM6 - PuTTY". The text displayed is: "User Name: To perform reset to factory defaults do not release the button for 10 seconds. Resetting local unit to Factory Defaults". Below this, there is a line of asterisks, followed by "SYSTEM RESET" in the center, and another line of asterisks. A green cursor is visible at the bottom left.

- houd de knop 10 seconden ingedrukt tot alle lichtjes branden
- nu wordt de switch reset naar **factory defaults**
 - standaard boot image
 - aanmaken RSA keys
 - standaard waarden herstellen

A screenshot of a PuTTY terminal window titled "COM6 - PuTTY". The text displayed includes: "Tapi Version: v1.9.6", "Core Version: v1.9.6", "06-Aug-2014 16:56:14 %INIT-I-InitCompleted: Initialization task is completed", "06-Aug-2014 16:56:27 %SNMP-I-CDBITEMSNUM: Number of running configuration items loaded: 0", "06-Aug-2014 16:56:27 %SNMP-I-CDBITEMSNUM: Number of startup configuration items loaded: 0", "The SSH Server is generating a default RSA key. This may take a few minutes, depending on the key size.", "The SSH Server is generating a default DSA key. This may take a few minutes, depending on the key size.", "The SSH Client is generating a default RSA key. This may take a few minutes, depending on the key size.", "The SSH Client is generating a default DSA key. This may take a few minutes, depending on the key size.", "06-Aug-2014 16:57:14 %SYSLOG-N-LOGGING: Logging started.", "06-Aug-2014 16:57:45 %SSL-I-SSLCTASK: Starting autogeneration of self-signed certificate - 1024 bits", "Generating RSA private key, 1024 bit long modulus", "06-Aug-2014 16:57:51 %SSL-I-SSLCTASK: Autogeneration of self-signed certificate was successfully completed", "Generating RSA private key, 1024 bit long modulus", "Console baud-rate auto detection is enabled, press Enter twice to complete the detection process", and "User Name:" with a green cursor.

- meld aan met cisco/cisco

meer info

voeg hier linken toe naar verdere uitleg

[cisco](#)

From:

<https://louslab.be/> - **Lou's lab**

Permanent link:

https://louslab.be/doku.php?id=cisco:reset_sg300-10&rev=1769543826

Last update: **2026/01/27 19:57**

