

reset SG300-10



context

dit document beschrijft hoe Cisco SG300-10 switch reset naar fabrieksinstellingen

stappenplan

- verbind de switch met je laptop ahv [console](#) kabel
- start de switch op
- druk met een paperclip de **reset**-knop ingedrukt

A screenshot of a PuTTY terminal window titled "COM6 - PuTTY". The text displayed is: "User Name: To perform reset to factory defaults do not release the button for 10 seconds. Resetting local unit to Factory Defaults". This is followed by a series of asterisks and the text "SYSTEM RESET" in the center, also surrounded by asterisks. A green cursor is visible at the bottom left.

- houd de knop 10 seconden ingedrukt tot alle lichtjes branden
- nu wordt de switch reset naar **factory defaults**
 - standaard boot image
 - aanmaken RSA keys
 - standaard waarden herstellen

A screenshot of a PuTTY terminal window titled "COM6 - PuTTY". The text shows the boot sequence: "Tapi Version: v1.9.6", "Core Version: v1.9.6", and a timestamp "06-Aug-2014 16:56:14 %INIT-I-InitCompleted: Initialization task is completed". It then reports on configuration items loaded (0 for both running and startup). Next, it shows the generation of default RSA and DSA keys for both the SSH Server and SSH Client, with timestamps. It then shows "Logging started" and "Autogeneration of self-signed certificate - 1024 bits". Finally, it shows "Autogeneration of self-signed certificate was successfully completed" and another RSA key generation step. The prompt "Console baud-rate auto detection is enabled, press Enter twice to complete the detection process" is shown. At the bottom, the "User Name:" prompt is visible with a green cursor.

- meld aan met **cisco/cisco**

- voer standaard [installatie switch](#) uit.

getest op

- Cisco SG300-10

meer info

voeg hier linken toe naar verdere uitleg

[cisco](#)

From:

<https://louslab.be/> - **Lou's lab**

Permanent link:

https://louslab.be/doku.php?id=cisco:reset_sg300-10&rev=1773513137

Last update: **2026/03/14 18:32**

