

tshark



context

dit document geeft enkele voorbeelden van tshark op Windows

algemeen

- open Powerhell-as-admin en voer uit: tshark

interfaces

- toon beschikbare interfaces

```
tshark.exe -D
1. \Device\NPF_{3A86E79A-7F23-4E5C-9E22-1408BFF518DD} (Local Area
Connection* 9)
2. \Device\NPF_{01D3BE70-4407-46DD-8503-6C71BDACA45F} (Local Area
Connection* 8)
3. \Device\NPF_{1F192FFE-43E8-4C71-90EE-6AC54CE8CFBD} (Local Area
Connection* 7)
4. \Device\NPF_{B4048E4F-0C6A-488F-9BC7-AE809EC8CE08} (Ethernet0)
5. \Device\NPF_Loopback (Adapter for loopback traffic capture)
6. etwdump (Event Tracing for Windows (ETW) reader)
```

- luister op specifieke NIC: tshark.exe -i <nummer>

redirect naar log

```
tshark -i 1 |tee -Append -FilePath <log>
```

voorbeeld:

```
tshark -i 1 hostname joske and port 22|tee -Append -FilePath
C:\Users\polleke\tshark.log
```

meer info

voeg hier linken toe naar verdere uitleg

[Linux](#)

From:

<https://louslab.be/> - **Lou's lab**

Permanent link:

https://louslab.be/doku.php?id=linux:tshark_op_windows&rev=1759477787

Last update: **2025/10/03 07:49**

